

Profile zamknięte prostokątne wg PN-EN 10219 w gat.S235JR								
Wymiary zewnętrzne [mm] / Grubość ścianek [mm]		1,5	2	2,5	3	4	5	6
30	15	S	S	P	P			
30	18	S	S	P	P			
30	20	S	S	P	S			
30	25	P	S	P	P			
35	20	P	P	P	P			
40	10	P	P	P	P			
40	20	S	S	P	S			
40	25	P	S	P	P			
40	27	P	S	P	S			
40	30	S	S	P	S			
45	25	P	P	P	P			
45	35	P	P	P	P			
50	20	S	S	P	S			
50	25	P	S	P	S			
50	30	S	S	P	S			
50	40	P	S	P	S	P		
50	45	P	P	P	P	P		
55	25	P	P	P	P	P		
55	35	P	P	P	P	P		
60	20	S	S	P	P	P		
60	30	S	S	P	S	P		
60	35	P	P	P	P	P		
60	40	S	S	P	S	P	S	P
60	50	P	P	P	S	P		
70	20	P	P	P	P	P		
70	25	P	P	P	P	P		
70	30	P	S	P	S	P	P	P
70	40	P	S	P	S	P		
70	50	P	S	P	S	P	P	P
70	60	P	P	P	P	P		
80	20	P	S	P	P	P		
80	30	P	S	P	S	P		
80	40	P	S	P	S	S	S	P
80	50		S	P	S	S		
80	60		S	P	S	S	P	P
90	20		P	P	P	P		
90	30		P	P	P	P	P	P
90	40		P	P	P	P		
90	50		P	P	P	P	P	P
90	60		P	P	P	P	P	P
90	70		P	P	P	P	P	P
100	20		S	P	P	P		
100	30		P	P	P	P		
100	40		S	P	S	P	P	P
100	50		S	P	S	S	S	P
100	60		S	P	S	S	S	P
120	40		S	P	S	P		
120	50		P	P	P	S	S	
120	60		P	P	S	S	S	
120	80		P	P	S	S	S	

Profile zamknięte kwadratowe wg PN-EN 10219 w gat.S235JR									
Wymiary zewnętrzne [mm] / Grubość ścianek [mm]		1,2	1,5	2	2,5	3	4	5	6
20	20	P	S	S	P	P			
25	25	P	S	S	P	S			
30	30	P	S	S	P	S			
35	35	P	S	S	P	S			
40	40		S	S	P	S	P	P	
45	45		P	S	P	S	P	P	
50	50		S	S	P	S	S	S	P
55	55			P	P	P	P	P	P
60	60		P	S	P	S	S	S	P
65	65			P	P	P	P	P	P
70	70			S	P	S	S	S	P
75	75			P	P	P	P	P	P
80	80			S	P	S	S	S	P
90	90			P		P	P	P	P
100	100			S	P	S	S	S	P

S – stan magazynowy P – produkcja pod zamówienie

DOM STALI
hurtownia stali precyzyjnej
www.domstali.pl