

Profile zamknięte wg PN-EN 10305-5 w gat. DC01						
Wymiary zewnętrzne [mm] / Grubość ścianki [mm]		0,8	1	1,2	1,5	2
10	10	P	S	P	P	
12	12	P	S	P	S	
14	14	P	S	S	S	
15	15	P	P	S	S	
16	16	P	S	P	S	
20	10	P	S	P	S	
20	15			S	S	
20	20	P	S	P	S	S
25	10				S	
25	15				S	S
25	20				S	S
25	25	P	S	S	S	S
30	10		S	S	S	S
30	15				S	S
30	18	P	P	S	S	S
30	20	P	P	P	S	S
30	25				S	
30	30	P	S	S	S	S
32	32	P	P	P	P	
35	20					S
35	25					S
35	35				S	S
40	10				S	S
40	15				S	S
40	20	P	P	P	S	S
40	25					S
40	30				S	S
40	40				S	S
45	20				S	S
45	25					S
45	45				S	S
50	15				S	S
50	20				S	S
50	25				S	S
50	30				S	S
50	40				S	S
50	50				S	S
60	15				S	S
60	20				P	S
60	30				P	S
60	40				S	
60	60				P	P

S – stan magazynowy P – produkcja pod zamówienie