

**Rury konstrukcyjne i przewodowe ze szwem wg PN-EN  
10217 i 10219 w gat. S235JRH/L235/P235TR1**

Wymiary zewnętrzne [mm] / Grubość ścianki [mm]	1,5	2	2,3	2,6	2,9	3,2	3,6	4	5	6,3	6,3
17,2		S	S	P	P						
18	S	S									
20	S	S									
21,3	S	S	P	P	P						
22	P	S									
25	S	S									
26,9		S	S	S	P	P	P				
33,7		S	S	S	S	P	P				
42,4		S	S	S	S	S	P	P			
48,3		S	P	S	S	S	P	P			
51		P	P	P	P	P	P	P	P		
60,3		P	P	P	S	P	S	P	P		
76,1		P	P	P	S	P	S	P	P		
80		S	P	P	P	P	P	P	P		
88,9		P	P	P	S	S	S	P	P		
101,6		P	P	P	P	P	S	S	P		
108						P	P	S	P		
114,3						P	S	P	S		
127						P	P	P	P		
133						P	S	S	P		
139,7						P	P	S	P		
159						P	P	P	P		
168,3						P	P	S	P		

**S – stan magazynowy**

**P – produkcja pod zamówienie**

# DOM STALI

hurtownia stali precyzyjnej

[www.domstali.pl](http://www.domstali.pl)