

**Rury przewodowe walcowane na gorąco
wg PN-EN 10216-1 w gat. P235 / wg PN-EN 10210-1,2 w gat. S235**

Wymiary zewnętrzne [mm] / Grubość ścianki [mm]	2	2,3	2,6	2,9	3,2	3,6	4	4,5	5	5,6	6,3	7,1	8	8,8	10	12,5	17,5
17,2	P	S	S	S													
21,3	P	S	S	S	S	S	S										
25		S	P	P	P	P	S	P	S								
26,9		S	S	S	P	S	S	P	S	S							
30			S	S	P	S	S	P	S	S	S						
31,8			S	P	P	P	S	S	P	P	S	S					
33,7			S	S	S	S	S	S	S	S	S	S					
38			S	S	S	S	S	S	S	S	S	S	S				
42,4			S	S	S	S	S	P	S	S	S	S	S	P			
44,5			S	S	P	P	S	P	S	S	S	P	P	P	P		
48,3			S	S	S	S	S	S	S	S	S	S	P	P	S		
51			P	S	S	P	S	P	P	S	S	S	P	P	S		
54				P	P	P	P	P	P	P	P	P	P	P	P		
57				S	S	P	S	P	P	P	S	P	P	P	S		
60,3				S	S	S	S	S	S	S	S	S	P	P	S		
63,5				P	S	S	P	P	S	P	S	S	S	P	S		
70				S	S	P	S	S	S	S	S	S	P	P	S		
76,1				P	S	S	S	P	S	S	P	S	P	P	S	S	S
82,5					P	S	P	P	S	P	P	P	S	P	S	S	
88,9					S	S	S	P	S	S	S	S	P	P	S	S	
101,6						P	S	P	S	S	S	P	P	P	S		
108						P	S	P	S	S	P	P	P	P	S	S	
114,3						P	S	P	S	P	S	S	S	P	S		
121									S		S						
127									S		S				S		
133								S	P	S	S				S		
139,7									S	S						P	
159							P		S		S		S				

S – stan magazynowy

P – produkcja pod zamówienie

DOM STALI

hurtownia stali precyzyjnej

www.domstali.pl